




RGBW LED Neon Color Change Flat



Technical Parameters

View	Sideview
Model No.	F15-RGBW
IC	without IC
Functions	color change
Controllers Used (see page 2)	F15A-C001: RGB Controller F15A-C002: Integration Controller F15A-C003: DMX Controller
Voltage	DC24V
Rated Power /M	14W
LED /M	60pcs 5050 SMD LED
RGB Wave Length	 R: 620-630nm;  G: 515-525nm;  B: 460-470nm
Chip Brand	Epistar
CRI	Ra>80
Lumen /M	Red: 35lm; Green: 110lm; Blue:18lm
Min Cutting Unit	6 LEDs
Min Cutting Length	10cm
Continuous Length	10m
Product Size	11.5x21mm
IP Rating	IP65 / IP68 optional
Packing Info.	50meters /reel /carton; 34x34x35cm; 21KG

Optional F15A Accessories

No.	Model.	Picture	Accessory
1	F15A-A001		Screw Front Connector Kit: 1x front connector 1x silicon gasket 1x anti-skidding clip 1x aluminum clip 4x 304 stainless screws
2	F15A-A002		Screw End Cap Kit: 1x end cap 1x silicon gasket 1x anti-skidding clip 1x aluminum clip 4x 304 stainless screws
3	F15A-A003		Clasp Front Connector Kit: 1x front connector 1x silicon gasket 1x anti-skidding clip 1x stainless clip
4	F15A-A004		Clasp End Cap Kit: 1x end cap 1x silicon gasket 1x anti-skidding clip 1x stainless clip
5	F15A-A005		Injection-moulded Front Connector Cable input side: right
6	F15A-A006		Injection-moulded Front Connector Cable input side: direct
7	F15A-A007		Injection-moulded Front Connector Cable input side: bottom
8	F15A-A008		Injection-moulded End Cap
9	F15A-A009		U-Shape Clasp Jumper: cable - 20cm 2x front connector 2x silicon gasket 2x anti-skidding clip 2x stainless clip

10	F15A-A010		T-Shape Clasp Jumper: cable - 20cm 3x front connector 3x silicon gasket 3x anti-skidding clip 3x stainless clip
11	F15A-A011		Aluminum Profile /1m
12	F15A-A012		Self-Locking Aluminum Profile /1m
13	F15A-A013		Aluminum Clip
14	F15A-A014		Self-Locking Aluminum Clip
15	F15A-A015		Seamless Middle Connector
16	F15A-A016		Seamless Power T-Feed
17	F15A-A017		Waterproof Glue
18	F15A-A018		Insert Inducer
19	F15A-A019		Cutter