

TECHNICAL DATA SHEET

DIGITAL Carpet Velours Type 2

DESCRIPTION:

DIGITAL Carpet Velours Type 2 is a white tufted pile carpet especially made for sublimation printers – also Solvent- Uv and latex printers. Ink will not scratch of, and drying time is minimal. It is best suited for indoor, digitally printed carpet or doormats. This Carpet is engineered for indoor use but can be used outdoors for short durations and is ideal for use corporate lobbies, waiting areas, foyers and trade show booth ad floor graphics.

PHYSICAL PROPERTIES:

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guaranty and do not constitute a warranty. Therefore, the results obtained from the use thereof, or that any use will not infringe upon any patent The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

| Characteristics | Test Method | Metric | English |
|-------------------|----------------------|---------------------|---------------------|
| Pile | N/A | 100% polyamide 6 | 100% polyamide 6 |
| Construction | N/A | Tuft special layer | tuft special layer |
| Total Height | N/A | 4 mm | 4 mm |
| Tuft Density | N/A | 165900 /m2 | 15412.5/sq.ft |
| Pile Weight | Din EN ISO 2286-2 | 500 g/m2 | 500 g/m2 |
| Total weight | Din EN ISO 2286-21 | 1.200 kg/m2 | 1.200 kg / m2 |
| Backing | ISO 13937-2-2002 | AB and Latex | AB and Latex |
| Pile Height | DIN 53351 | 3 mm | 3 mm |
| Width | DIN EN ISO 2286-1 | 320/200/160/110/130 | 320/200/160/110/130 |
| Roll length | 25 | 25 | 25 |
| Fastness to Light | ISO 105 B01 (1 tm 8) | < 5 | < 5 |
| Fire Resistance | DIN 4102 | norm Bfl / s1 | norm Bfl / s1 |

Printingcarpets.com
[Bet you can print on it]